

Lambert® PU Primer MP

Multi-purpose Primer for PU Waterproofing Membrane and Joint Sealant

Product description	Single component polyurethane based multi-purpose primer.
Uses	Lambert PU Primer MP is used to improve adhesion when applying one or two component polyurethane waterproofing coating or polyurethane based joint sealant. Lambert PU Primer MP can be used to metal or mineral substrates
Advantages	<ul style="list-style-type: none">❖ Enhance bond strength❖ Easy to apply by brush or roller❖ Fast drying❖ Low viscosity❖ Ideal for priming new or existing, horizontal or vertical, interior or exterior concrete surfaces, steel, tiles, sheet piles, galvanized sheeting, slate, plywood decks, polypropylene sheet, zinc, aluminium
Technical Data	
Colour	Transparent
Type	Liquid
Viscosity	15 ± 2 mPa·s
Solid Content	45 ± 3%
Curing Time	Touch dry 2 hours
	Fully cured 24 hours
VOC Content	<65%

Application

Substrate must be clean, dry and free from all traces of grease, oil and dust. Loose particles and coating must be completely removed. Maximum admissible substrate moisture content 8%.

Apply Lambert PU Primer MP in fair weather when the surface and air temperatures are 4°C and rising. Apply with a sprayer, roller or brush at a coverage rate of 5m²/kg. Prime only the area to be covered with the waterproofing membrane or joint sealant during the working day. Areas not covered with a membrane or sealant in 24 hours must be re-primed.

Dries in approximately one hour, depending on temperature and application rate. Must be tacky to the touch before covering. If the work area is very dusty, apply membrane or sealant as soon as possible after Lambert PU Primer MP is dry.

Supply	10 kg metal drum
Storage	Stored in unopened original containers, in dry conditions at temperatures between +10°C and 25°C. Shelf life is 12 months.
Precautions	Lambert PU Primer MP contains volatile, flammable liquids. Keep away from open flames. Only use in well ventilated areas. Wear goggles and gloves during application.
Notes	The information, and, in particular, the recommendations relating to the application and end use of Lambert products, are given in good faith based on Lambert's knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respects of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Distributor:

AGENCIA COMERCIAL KIN CHEUNG
 AVN. GOV. J. S. MARQUES NO. 253
 R/C "A1" KIN HENG LONG PLAZA
 MACAU
 T : (853) 28424080
 F : (853) 28424081
 E : info@kincheung.com